

weber geokeçe

Waterproofing fleece

Technical Data Sheet
Issued on : 20.01.2016
Revision No: 004

■ Description

weber geokeçe, which is fleece type made of non-woven polyester fibers, reinforces the waterproofing layer.

■ Advantages

- Easy application
- Long life
- Resistant to chemicals

■ Range of application

- Used as reinforcement middle layer between liquid resin waterproofing products such as polyurethanes and elastomeric. Also used for obtaining homogenous thickness for the products.

■ Performance

- Weight : 45 gr/m².
- Thickness: 0,25 mm.
- Width : 1,5 mt.
- Tensile Strength > 2,00 kN/m (TS EN ISO 103819).
- Extension at Break Strength > %50 (TS EN ISO 103819).

■ Application

- Used as laying out quickly after on the first waterproofing coating in smooth way. Should obtain high adherence with first waterproofing coat with the help of brush or trowel. Next waterproofing coat should be applied over the fleece on complete substrate.

■ Packaging

Roll : 100 linear mt (150 m²).

■ Shelf life

2 years

- > The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.
- > **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemaipaşa OSB Mah. Kuyucak Yolu Sokak No: 284 • 35730 Kemaipaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.weber.com.tr • info@weber.com.tr • Çözüm hattı: 444 6 990

