

weber KA 2000

Mineral oil based mould release agent

Technical Data Sheet
Issued on : 07.09.2015
Revision No: 003

■ Description

Mineral oil based, mould release agent giving smooth and even surface to the concrete and releasing the mould from the fresh concrete easily.

■ Advantages

- Fast and easy release of non-absorbent steel, plastic, plywood moulds or wooden moulds from the concrete.
- Increases service life and efficiency of moulds.
- Decreases mould cost and labor significantly in constructions.
- Smooth and clean concrete substrate.

■ Range of application

- It is used for increasing service life of mould, removal of concrete smoothly and saving from labor.

■ Application substrates

- Tunnel moulds
- Steel moulds
- Plywood moulds
- Plastic moulds
- Wooden moulds
- Please consult us for all other application substrates.

■ Reference standarts

- Public Work Pos. No: 04.116/2

■ Attention points

- Use gloves and goggles during the application and avoid eye and skin contact.

■ Conditions of application

- The ambient temperature is between: +5 °C and +35 °C.
- Moulds should be clean and dry, there should not be chemical residuals from previous application for good performance.
- Concrete should be cleaned from rust and residuals.
- **weber KA 2000** is ready to use, it should be shaken a little before the application.

■ Application

- **weber KA 2000** should be applied on clean mould surfaces via spraying, roller or brush directly.
- For maximum benefit from the product, the material should be applied in a thin layer. Since excessive oil use will cause stain on concrete, excessive oil on the substrate should be made in ideal amount with sponge or similar material.
- The second layer application may be necessary on very absorbent substrates.

■ Consumption

About 20 m²/1 lt
(on absorbent substrate such as wooden, etc.)
About 40 m²/1 lt
(on non-absorbent substrate such as plastic, steel, etc.)

■ Packaging

30 lt plastic plastic drums,
210 lt plastic barrels.

■ Color

Yellow.

■ Application tools

Spray, brush, roller and sponge.

■ Shelf life

24 months as of the production date in dry and moisture-free environment provided that packages will not be opened and kept between 5 °C and 35 °C. Package should be kept tightly closed when not in use.

➤ The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

➤ **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No: 284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.weber.com.tr • info@weber.com.tr • Çözüm hattı: 444 6 990

