

MAPESENT PANEL

Dry soundproofing system formed by 1 m by 1 m tiles for floating screeds



WHERE TO USE

Dry soundproofing system with a reduced thickness (13 mm), to reduce noise transmitted by footsteps between adjacent housing units. Applied on floating screeds before laying all kinds of flooring material (ceramic tiles, stone, resilient and fabric floor coverings, wooden floors, etc.).

Mapesilent Panel is applied between the structure and the floating screed.

Some application examples

Soundproofing all types of floor slabs.

TECHNICAL CHARACTERISTICS

Mapesilent Panel tiles are composed of a bitumen and special polymer-based elasto-plastomeric membrane, sandwiched together with a resilient layer of polyester fibre.

Because of its low thickness, **Mapesilent Panel** has no effect on the final project dimensions and elevations. Also, its high resistance to footsteps and tools dropped accidentally on the layer prevents it being damaged and reducing its soundproofing capacity.

Mapesilent Panel offers a simple, reliable and efficient method to form a floating screed which is perfectly insulated from the support structure (floor slab + separating walls).

By sandwiching the polymer bitumen membrane with polyester fibres, noises are absorbed and reduced so that certain types of floor slab, including those in the following table, meet the requirements according to current norms and regarding acoustic insulation against noise transmitted by footsteps.

Thanks to the higher thickness of the polyester fibre (10 mm), **Mapesilent Panel** also has the capacity of improving the thermal transmittance value (U) of floor slabs.

In order to avoid the formation of acoustic bridges, a soundproofing system using **Mapesilent Panel** also requires the use of other products from the range: **Mapesilent Band R** and **Mapesilent Tape**, as described below.

RECOMMENDATIONS

- Must not be used for soundproofing purposes directly below the final coating (in this case, use **Mapesonic CR**).
- The thickness and, where required, reinforcement of screeds installed on top of **Mapesilent Panel**, must be calculated according to the stresses on the surface when in service and on the type of coating laid on the floor.

PREPARATION OF THE SUBSTRATE

Make sure the substrate is flat and strong and that there are no rough spots.

Any excess material which makes the surface uneven must be removed.

Uneven surfaces and areas where plant fittings pass through (such as electric cables and pipework) the substrate must be evened out before laying **Mapesilent Panel**.

To make screeds and even out laying surfaces please refer to the catalogues which illustrate the various ranges of MAPEI products for the preparation of substrates or contact the MAPEI Technical Assistance Department.

APPLICATION PROCEDURE

Lay the **Mapesilent Panel** tiles with the polyester fibre layer (the light-coloured side) towards the bottom, making sure they are perfectly aligned. Seal all the joints between the tiles of **Mapesilent Panel** with **Mapesilent Tape** (closed-cell, foam polyethylene adhesive sealing tape).

If better insulation or soundproofing are required, the efficiency of the insulating material may be increased by laying a double layer with the white sides laid against each other, by applying the first layer white side up.

The perimeter of the room to be soundproofed must be insulated using **Mapesilent Band R** (closed-cell foam polyethylene adhesive tape applied around the perimeter of walls and elements which pass through the screed, to avoid the formation of acoustic bridges).

Mapesilent Band R is available in 100 and 160 mm wide rolls. The 160 mm version is used mainly on heating screed.

Seal all the joints between the various pieces of **Mapesilent Band R** and between **Mapesilent Band R** and **Mapesilent Panel**.

Once the final floor covering has been laid, and immediately before attaching the skirting boards, cut the excess pieces of **Mapesilent Band R**, seal the spaces between the skirting boards and the floor with a suitable flexible sealant.

Do not install the system if the temperature is too high or too low, and in all cases, do not carry out any operations which could perforate the soundproofing system.

PACKAGING

Mapesilent Panel is available on pallets with 75 tiles, which cover an area of 75 m².

STORAGE

12 months in its original packaging in a dry place protected from direct sunlight with the exception of **Mapesilent Band R** and **Mapesilent Tape**, which can be stored for 9 months.

Do not stack the pallets on top of each other. Contact with solvents or organic liquids may damage the product.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Mapesilent Panel is an article and referring to the current European regulations (Reg. 1906/2007/CE - REACH) does not require the preparation of the material Safety Data Sheet. During use it is recommended to wear protective gloves and goggles and follow the safety requirements of the workplace.

PRODUCT FOR PROFESSIONAL USE.


TECHNICAL DATA (typical values)			
Test method	Technical characteristics	Unit of measure	Value
EN 29073-2	Thickness	mm	13.0 (before sandwiching)
EN 1849-1	Weight	kg/m ²	5.0
EN 12311-1	Longitudinal tensile strength	N/50 mm	700
EN 12311-1	Transversal tensile strength	N/50 mm	500
EN 12691	Impact strength	mm	900
EN 12730	Static perforation strength	kg	15
EN 1928	Impermeability to water	kPa	≥ 100
EN 13501-1	Fire resistance		F
EN 12667	Thermal resistance	m ² K/W	0.313
EN 29052-1	Dynamic stiffness for calculation purposes (S')	MN/m ³	13 ⁽¹⁾

EN ISO 12354-2	Estimated reduction of noise due to footsteps (ΔL_w)	dB	31.1 ⁽²⁾
Sound level measurement	Reduction of noise caused by footsteps (ΔL_w) measured on site	dB	up to 42.0 ⁽³⁾


(1) Certified by independent lab. - n. 004-2021-RIG

(2) Simplified calculation method valid for 100 kg/m² floating screeds with ceramic flooring

(3) Sound level measurements taken in situ on a brick-cement floor slab were carried out by a qualified Environmental Acoustics Technician



Lay the Mapesilent Panel tiles with the fibre layer (the light-coloured side) towards the bottom, making sure they are perfectly aligned



Once alignment of the Mapesilent Panel tiles has been checked, carefully seal all the joints using Mapesilent Tape




To guarantee that Mapesilent Tape bonds perfectly, we recommend passing over the surface of the tape with a rigid or semi-rigid roller



Cut the lower part of Mapesilent Band R to form a 90° angle and remove the protective backing film to expose the adhesive part



Position the angle of Mapesilent Band R in order to check that the two sides of the cut match perfectly



Apply Mapesilent Tape along the overlaps of Mapesilent Panel and Mapesilent Band R and the joints between the various sections of Mapesilent Band R



Once work has been completed, Mapesilent Tape must be visible on all the overlaps and joints of Mapesilent Panel and Mapesilent Band R. There must be absolutely no contact points with the substrate, to avoid the formation of acoustic bridges

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to

confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at www.mapei.com. ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.

912-5-2021-gb

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

